

Model :H3TX-2U

Specifications:	
Function	ON-OFF temperature controller SELF TUNE temperature controller.
Rated Supply Voltage	85V to 270V AC/DC
Rated Frequency	50/60 Hz $\pm 5\%$ for AC only
Power consumption	AC Aprox.4VA / 1W
Control Output	1 C/O contact rated for 5A@250V AC/28V DC resistive load.
Display accuracy	$\pm(0.5\%$ of full scale) $\pm 1^{\circ}$ C
Hysteresis	2° C - 20° C (for ON/OFF function only)
Range	0° C - 600° C (J TYPE) 0° C - 1200° C (K TYPE) -100° C - 300° C (PT100 ON/OFF) 0° C - 300° C (PT100 SELF TUNE)
Input	J/K/PT100
Recovery Time	2 Sec minimum
Ambient temperature	Operation : $+5^{\circ}$ C to $+45^{\circ}$ C Storage : -10° C to $+85^{\circ}$ C
Variation due to temperature	0.25° C per degree change in ambient temperature (ref. 25° C)
Humidity	Up to 85% RH @ 40° C
Insulation resistance	>100 M ohms @ 500V DC
Service life (under no load)	10^6 operations minimum
Electrical life(under full load)	10^5 operations minimum
Dielectric strength	a) 2.5 KV AC, 50HZ for 1 minute. (Between current carrying & non-current carrying parts) b) 1.5 KV AC, 50HZ for 1 minute. (Between contacts & control circuit) c) 750 V AC, 50HZ for 1 Minute. (Between non-continuous relay contacts)
Electrical Connection	Screw type terminals with self lifting clamps.
Dimension	48 x 48 x 115 mm(W x H x D)
Enclosure(series)	H1D-Series(long box)



DIGITAL PROMOTERS (INDIA) PRIVATE LIMITED

502 & 505, Vishal Bhawan,95 Nehru Place, New Delhi-110 019, INDIA
Ph. : 41618100 (3 Lines), 011-26418118 Fax : 26437849
Email : digitalpromoters@gmail.com • info@digitalpromoters.com
Website : www.DigitalPromoters.com

