

## testo 460

testo 460 optically measures rpm, e.g. of ventilators and shafts. The measurement spot is displayed on the measurement object with an LED marking. Max./min. values are displayed directly at the press of a button. The backlit display allows the measurement values to be easily read out, even in unfavourable light conditions. testo 460 is very handy, small and easy to operate.

testo 460; rpm measuring instrument incl. protective cap, batteries and calibration protocol

Part no.

**0560 0460**

### Technical data

Meas. range	100 to 29999 rpm
Accuracy	±(0.02 % of mv + 1 Digit)
Resolution	0.1 rpm (100 to 999.9 rpm) 1 rpm (1000 to 29.999 rpm)
Selectable units	rpm, rps
Measuring rate	0.5 s
Protection class	IP40

## Pocket-sized measuring instrument for non-contact rpm measurement

- Optical rpm measurement with LED measurement spot marking
- Max./min. values
- Display light
- Protective cap for safe storage
- Incl. calibration protocol



### Accessories

Reflectors, self-adhesive (1 pack = 5 off, each 150 mm long)

Part no.

0554 0493

### Calibration Certificates

#### Accessories and Technical data

ISO calibration certificate/rpm  
Calibration points freely selectable from 10 to 99500 rpm

Part no.

0520 0114

Oper. temp.	0 to +50 °C
Storage temp.	-40 to +70 °C
Battery type	2 batteries Type AAA
Weight	85 g (incl. battery and protective cap)
Warranty	2 years
Dimensions	119 x 46 x 25 mm (incl. protective cap)
Battery life	20 h (average, without display illumination)